

ROLLE 8



HALOILA

Machines & Service

www.haloila.com

ROLLE 8

IS DURABLE AND EASY TO USE

When the most important criteria are ease of use and robust machine, Rolle 8 is ideal for these applications.


Fast and easy to use

- 1. Wrapping can be started by selecting light or strong wrapping and then start.**
 - If necessary, wrapping can be interrupted for the palletisation of products by means of the pause function.



The film can be conveniently adjusted

- 2. The film tension can be adjusted by means of a separate brake roller.**
 - A change in the diameter of the film roll does not affect the film tension in the product pallet.
 - The film roll is easy to change.
 - The brake roller can be released to make it easier to fix the film in the product pallet.
 - The height of the product pallet is detected by means of a photocell.



Turntable

- 3. The rotating of the turntable is controlled by a frequency controller. This reduces mechanical stress and the need for maintenance.**
 - Thanks to the stepless control of the rotational speed and the smooth start-up of the machine, it is also possible to wrap unstable product pallets.
 - The turntable always stops in the same place. This makes it possible to use a ramp, which is available as an option.



Technical data

Power supply	220–240V / 50 Hz	Rotation speed	1–11 rpm
Machine dimensions	2575 x 1650 mm	Max pallet load dim.	1200 x 1000 mm
Max height	3000 mm	Wrapping height	50–2600 mm
Turn table Ø	1650 mm	Max. pallet load weight	1200 kg
Turn table height	80 mm	Film reel Ø	<260 mm
Weight	360 kg		

Rolle 8 fits into a small space and is easy to transport and install.



HALOILA

Machines & Service

Haloila, FI-21250 Masku (Finland), Tel.: (+358) 2 437 6111, Fax: (+358) 2 437 6211
octopus.gb@team.haloila.com octopus.global@team.haloila.com www.haloila.com